

INTERMEDIATE BULK CONTAINERS



Introduced over 50 years ago as an efficient alternative to traditional containers, the Liquitote is still the leading metal IBC in the market today. Hoover's advanced manufacturing technology provides a one-piece Liquitote body and single-seam welding, offering greater strength due to a 50% less weld area. Built to last in an ISO 9001 certified plant, this IBC's 10 gauge stainless or carbon steel construction and patented one-piece sloped bottom has made it the superior choice for storage and transportation in the oil and gas, chemical, and petrochemical markets. Reusable, easy to clean, and durable, the Liquitote is a sound investment which can be amortized over its life cycle.

DESCRIPTION

- UN/DOT compliant with UN markings
- 10 gauge, 304 stainless steel with 2B finish
- · One piece body and single seam welding
- Sloped bottom for virtual 100% discharge
- 22-5/16" (566 mm) top manway with EPDM gasket and bolted clamp ring
- 3" fusible cap with lanyard
- 2" (50.8 mm) top bung fitting with EPDM gasket
- Stainless steel UN tag
- · Heavy duty lifting lugs/stackable leg positioners
- 2" (50.8 mm) discharge assembly with 316 stainless steel one piece elbow, locking handle ball valve and plastic plug
- Full-length valve guard on side drain tanks
- 6-1/2" (height) (166 mm) radius corner legs with caps 9-1/4" (235 mm on center drain tanks)
- Three-way fork lift entry on side drain tanks
- 350 and 550 gallon models feature a one-piece body and single-seam welding
- Stackable

APPLICATIONS

Hoover stainless steel IBC's are rated UN31A for the transportation and storage of hazardous and non-hazardous liquid chemicals. Hoover IBCs are used for a variety of applications including:

- Combustible and flammable raw materials
- Solvents and solvent based chemical preparations
- · Water treatment chemicals
- · Oil and water based lubricants
- · Down hole chemicals
- · Paints and allied products
- Resins
- · Pigments and dyes
- · Cleaning and sanitation chemicals
- · Pharmaceutical and food preparations
- · Industrial organics



350 Gallon - Side Drain Product Number 370494



550 Gallon - Center Drain Product Number 372412



793 Gallon Center DrainProduct Number 372422

LIQUITOTE® THE ORIGINAL IBC

Liquitote, the leading stainless steel IBC on the market, is the original intermediate bulk container (IBC) of the liquid handling industry. Hoover introduced this revolutionary concept over 50 years ago as an efficient and sensible alternative to the use of 55 gallon drums. One 550 gallon Liquitote tank replaces ten drums minimizing the amount of handling required, which in turn, saves money and lowers the risk of liquid handling accidents.

IBCs INCREASE SAFETY AND REDUCE YOUR COST COMPARED TO DRUMS



Cargo Valve IBC
Product Number 372102



3" Fill Cap



Side Drain
Discharge Assembly



Drum Cover



Center Drain
Discharge Assembly



2" Top Bung



Lifting Lugs

SIDE DRAIN SPECIFICATIONS											
NOMINAL CAPACITY	NOMINAL LENGTH	NOMINAL WIDTH	NOMINAL HEIGHT	APPROX TARE WEIGHT	MAXIMUM GROSS WEIGHT	DRAIN	PRODUCT NUMBER				
120 gal (454 l)	42" (1067 mm)	48" (1219 mm)	24.5" (622 mm)	286 lbs (130 kg)	2,205 lbs (1000 kg)	Side Drain	370542				
180 gal (681 l)	42" (1067 mm)	48" (1291 mm)	31.5 (800 mm)	347 lbs (157 kg)	3,196 lbs (1450 kg)	Side Drain	370967				
300 gal (1135 l)	42" (1067 mm)	48" (1219 mm)	45" (1143 mm)	430 lbs (195 kg)	5,203 lbs (2360 kg)	Side Drain	370470				
350 gal (1325 l)	42" (1067 mm)	48" (1219 mm)	51" (1295 mm)	475 lbs (215 kg)	6,030 lbs (2735 kg)	Side Drain	370494				
400 gal (1514 l)	42" (1067 mm)	48" (1219 mm)	57" (1448 mm)	534 lbs (242 kg)	6,867 lbs (3115 kg)	Side Drain	370968				
450 gal (1703 l)	42" (1067 mm)	48" (1219 mm)	63" (1600 mm)	594 lbs (269 kg)	7,694 lbs (3490 kg)	Side Drain	370544				
550 gal (2082 l)	42" (1067 mm)	48" (1219 mm)	75" (1905 mm)	630 lbs (286 kg)	9,370 lbs (4250 kg)	Side Drain	370489				
793 gal (3000 l)	54" (1372 mm)	54" (1372 mm)	75" (1905 mm)	795 lbs (361 kg)	13,456 lbs (6104 kg)	Side Drain	372292				

CENTER DRAIN SPECIFICATIONS											
NOMINAL CAPACITY	NOMINAL LENGTH	NOMINAL WIDTH	NOMINAL HEIGHT	APPROX TARE WEIGHT	MAXIMUM GROSS WEIGHT	DRAIN	PRODUCT NUMBER				
350 gal (1325 l)	42" (1067 mm)	48" (1219 mm)	53.75" (1365 mm)	575 lbs (261 kg)	6,030 lbs (2735 kg)	Center Drain	372086				
550 gal (2082 l)	42" (1067 mm)	48" (1219 mm)	77.75" (1975 mm)	665 lbs (302 kg)	9,370 lbs (4250 kg)	Center Drain	372412				
793 gal (3000 l) 2-way fork channel	54" (1372 mm)	54" (1372 mm)	77.75" (1975 mm)	866 lbs (393 kg)	13,456 lbs (6104 kg)	Center Drain	372422				
793 gal (3000 l) 4-way fork channel	54" (1372 mm)	54" (1372 mm)	77.75" (1975 mm)	1,047 lbs (475 kg)	13,456 lbs (6104 kg)	Center Drain	372388				

Custom sizes are available to meet your specific needs

North America

Houston, TX +1 800.844.8683 Midland, TX +1 832.920.1275 Scott, LA +1 337.552.2120 New Iberia, LA +1 337.369.7098 Port Fourchon, LA +1 985.396.4545 Eastern Region 888.826.8683 Western Region 800.844.8683

Europe

Stavanger, Norway +47 51 71 58 80 Człuchów, Poland +48 728 201 709

United Kingdom

Aberdeen, Scotland +44 1224 894222

South America

Macae, Brazil +55 22 3518 2911

Asia Pacific

 Kuala Lumpur, Malaysia
 +603 2168 1824

 Melbourne, Australia
 +613 9325 1135

 Perth, Australia
 +1800 731 948

Middle East

Abu Dhabi, UAE +971 2 6171000

